


N 1 N 2 N 3 N 4 N 5 N 6
GVS

注意事项

1、请远离强磁场、高温、潮湿等环境；



9

57Y DF 563Y DF 0HG

9 HQ 93 : 48 68

NQ [

1nq{surg


HWV HWV81:


9

-
-
-

-
-
-
-
-
-
-
-

	54063Y GF
	?4618 p D257Y ?4418 p D263Y ?678 p Z
	57Y 2 563Y DF
	9
	φ633 p D 68⇊ 57Y 2 563Y DF 2
NQ [	+ 2 ,
2	3150518 p p 5 317Q0 p
OHG	
OHG 2 2 2 OHG 2	
	_8 3F 111 . 78 3F
	_58 3F 111 . 88 3F _ 58 3F 111 . :3 3F
	?<6 (/
	68 p p
:5 { <3 { 97 p p	
316NJ	





57Y 2 563Y Q Q

4¢9 2 Dooo rq Dooo rii OHG

2 2 OHG 4 4

2 Pdq1

4 2

OHG

2

9

SL

9

2 2 7

SL

8

❖ VN @

✧ HWV 814 +5,

TU



814+5, Dgg Ghylfh Fhuwlilfdwh

✧ HWV

I'







814+9,

†Dgg Ghylfh Fhuwlilfdwh‡

C



-.-.- Heating Actuator with Triac, 6-Fold > General
KNX Secure
Send delay after voltage recovery [0..15]
5
s
Send cycle of "In operation" telegram
(1..240.0=inactive)
Thermal




2 †Vxpphu2Zlqwhu prgh‡

HWV

†Xqfkdqjh‡ 3



RxwsxwOrfdo frqwurohu



RxwsxwOH{whuqdo frqwurohu

816 †Rxwsxw {‡

2

2

A3 (3 (

Uhvsrqg diwhu uhdg rq0|

†Frqwur0 yd0xh idx0w‡

Uhvsrqg diwhu fkdqjh

t3 †Frqwur0 yd0xh


idx0w‡

Frq qxrxv SZP+xvlS fr wur,


SZP

†H{whuqd frqwurohu‡

†Qrup d+gh0hqhujlvhg forvhg,‡



Uhvsrq Ò}hypÚ V




7


†Glvde◊h‡

†Irufhg rshudwlrq‡

2 2

4elw A3(3(








81714 †Jhqhudo vhwwlqj‡

5


3




2 2


3 3 3

4



, I EXRU E Eg" I






QSHV

†Khdwlqj dqg Frrolqj‡ †Dxwr pdwlf fkdqjhryhu‡


2

.


0



81715+4, Vhws r IqwbUhodwlyh‡




81715+5, †Vhwsrlqwbevroxwh‡




Kı.


Frr0lqj





Note: The heating setpoint must be always less than the cooling setpoint.

2 2





†Vzlwfklqj rq2rii+xvh50srlqw frqwur0,‡




†Vzlwfklqj SZP+xvh SL frqwur0,‡

4N 5N 55 W 57

W 54 @W 54¢57

4N 5N 59 W




	8N	573 p lq	S Z P	48053 p Lq
	7N	<3 p lq	S Z P	43048 p lq

†Khdwlqj2Frr olqj vshhg‡ †Xvhu ghilqhg‡ S

L SL

3



81716+6, SL

\

\4

[4 @ ‘

[5 @ ‘


WQ

N

SL \@N-+[40[5 .[4-N-w2WQ.\4

SL \@N [40[5 .\5


N=	
N=	
W_Q=	
W_Q=	





81717 Vfhqh‡

8

3


The setpoint is less than minimum,so minimum will regard as setpoint in fact


The setpoint is greater than maximum,so maximum will regard as setpoint in fact



Number	Name	Object Function	Description	Group Address	Length	C	R	W	T	U	Data Type	Priority
1	General	In operation			1 bit	C	R	-	T	-	switch	Low
2	General	Summer/Winter mode			1 bit	C	-	W	T	U	switch	Low
3	General	Status of operating voltage failure			1 bit	C	R	-	T	-	alarm	Low

914 †Jhqhud‡

					GSW
†4‡					
2					

57Y 563Y

4 ‘ ‘


3 ‘ ‘

57Y DF 518Y 7;Y 518Y

7;Y

563Y DF 7;Y 7;Y

914 †Jhqhud‡



915 †Rxwsxw‡

†H{whuqdo frqwurohu‡ 4elw

4e|wh SL

†Ghvfulswlrq +pd{ 63fkdu1,‡ †Rxwsxw

40111‡


4 ‘ ‘

3 ‘ ‘

4 ‘ ‘

3 ‘ ‘

915 †rxwsxw‡



Number	Name	Object Function	Description	Group Address	Length	C	R	W	T	U	Data Type	Priority
65												
		Base setpoint adjustment			2 bytes	C	-	W	-	-	temperature (°C)	Low
68	Controller 1-...	Setpoint offset			1 bit	C	-	W	-	-	step	Low
69	Controller 1-...	Float offset value			2 bytes	C	-	W	-	-	temperature differ	Low
		Heating/Cooling mode			1 bit	C	-	W	-	-	cooling/heating	Low
72	Controller 1-...	Operation mode			1 byte	C	-	W	-	-	HVAC mode	Low
73	Controller 1-...	Comfort mode			1 bit	C					enable	Low
91	Controller 1-...	Heating control value			1 bit	C	R	-	T	-	switch	Low
92	Controller 1-...	Cooling control value			1 bit	C	R	-	T	-	switch	Low

916 †Frqwurohu‡

4e|wh :5 40 50 60 70

4elw

:6 ‘ ‘

:7 ‘ ‘

:8 ‘ ‘

:9 ‘ ‘

†4‡ 4elw 3

4elw †4‡ 3

4 ‘ ‘

3 ‘ ‘

4 4

2

2

4 ‘ ‘

3 ‘ ‘

4 ‘ ‘

3 ‘ ‘
